

# PRODUCT DATASHEET

## MS-SV INF-CR-A 360 220-240 V IP20

LED VALUE PIR Motion Sensor | Sensors with infrared technology



---

### Areas of application

- Suitable for indoor applications
- Offices
- Corridors
- Stairways
- Residential interiors
- Commercial buildings

---

### Product features

- 360° motion sensor (passive infrared technology)
- Ceiling surface and recessed mounting
- Timer function
- Adjustable illuminance from 3 or 10 lx to 2000 lx via knob switch (model dependent)
- Photocell detector available for daylight detection
- Input voltage: 220...240 V<sub>AC</sub>
- Operating frequency: 50/60 Hz
- Ambient temperature in operation: -20...+40 °C
- Type of protection: IP20

---

## TECHNICAL DATA

### Electrical data

Nominal voltage	220...240 V
Type of current	AC
Mains frequency	50...60 Hz
Surge capability (L-N)	1 kV

### Dimensions & Weight

Length	70.00 mm
Width	80.00 mm
Height	62.00 mm
Product weight	69.3 g

### Colors & materials

Product color	White
---------------	-------

### Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
---------------------------	--------------

### Capabilities

Dimmable	No
Maximum installation height	2.2...4 m
Detection area	8 m <sup>1)</sup>
Detection angle	360 °

<sup>1)</sup> Maximum diameter

### Certificates & Standards

Protection class	II
Type of protection	IP20

### LOGISTICAL DATA

Temperature range at storage	-35...+55 °C
------------------------------	--------------

---

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075373013	Folding box 1	85 mm x 64 mm x 96 mm	93.00 g	0.52 dm <sup>3</sup>
4058075373020	Shipping box 10	332 mm x 182 mm x 116 mm	1105.00 g	7.01 dm <sup>3</sup>

# 403 Forbidden

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

**403 Forbidden**