

# PRODUCT DATASHEET

## LED Value Slim Downlight 9 W/6500 K

LED VALUE SLIM DOWNLIGHT | Flat downlight luminaires



### Areas of application

- Corridors, entrance areas
- Foyers
- Elevators
- Retail

### Product benefits

- Die-cast aluminum housing for improved heat dissipation
- No light can escape at the back of the luminaires thanks a special cover
- Elegant design

### Product features

- Product color: white
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Color rendering index  $R_a$ : > 80
- High color consistency:  $\leq 6$  SDCM
- Luminaire efficacy: up to 89 lm/W
- Type of protection: IP20
- Lifetime (L70/B50): up to 30,000 h
- Protection class: II
- Uniform illumination



## TECHNICAL DATA

### Electrical data

Nominal wattage	9.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor $\lambda$	0.50
Protection class	II

### Photometrical data

Luminous flux	600 lm
Luminous efficacy	67 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Standard deviation of color matching	$\leq 6$ sdc <sub>m</sub>
Beam angle	120 °

### Dimensions & Weight

Length	120.00 mm
Width	120.00 mm
Height	20.00 mm
Product weight	165.00 g

LDVAL SLIM downlight SQ 105 9W

### Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Plastic

Mercury content	0.0 mg
-----------------	--------

### Application & Mounting


Ambient temperature range	-10...+50 °C
Temperature range at storage	-20...+70 °C
Type of protection	IP20
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting length	105.00 mm
Mounting width	105.00 mm
LED module replaceable	Not replaceable

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h <sup>1)</sup>
Number of switching cycles	25000

1) t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

### DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES file (IES)	LDVAL SLIMDL SQ 105 9W 865

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075314337	Folding box 1	162 mm x 47 mm x 125 mm	215.00 g	0.95 dm <sup>3</sup>
4058075314344	Shipping box 20	338 mm x 253 mm x 266 mm	4705.00 g	22.75 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

