

PRODUCT DATASHEET

LED Value Slim Downlight 4 W/6500 K

LED VALUE SLIM DOWNLIGHT | Flat downlight luminaires



Areas of application

- Corridors, entrance areas
- Foyers
- Elevators
- Retail

Product benefits

- Die-cast aluminum housing for improved heat dissipation
- No light can escape at the back of the luminaires thanks a special cover
- Elegant design

Product features

- Product color: white
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Color rendering index R_a : > 80
- High color consistency: ≤ 6 SDCM
- Luminaire efficacy: up to 89 lm/W
- Type of protection: IP20
- Lifetime (L70/B50): up to 30,000 h
- Protection class: II
- Uniform illumination



TECHNICAL DATA

Electrical data

Nominal wattage	4.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	35.000 mA
Power factor λ	0.50
Protection class	II

Photometrical data

Luminous flux	200 lm
Luminous efficacy	50 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Standard deviation of color matching	≤ 6 sdc _m
Beam angle	120 °

Dimensions & Weight

Length	85.00 mm
Width	85.00 mm
Height	20.00 mm
Product weight	155.00 g

LDVAL SLIM DOWNLIGHT SQ 70
4W

Materials & Colors

Product color	White
Housing color	White

Body material	Aluminum
Cover material	Plastic
Mercury content	0.0 mg

Application & Mounting


Ambient temperature range	-10...+50 °C
Temperature range at storage	-20...+70 °C
Type of protection	IP20
Dimmable	No
Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting length	70,0 mm
Mounting width	70,0 mm
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	50000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta, t[h]; L80 / B10 @ 25 °C (Ta, t[h]; L90 / B10 @ 25 °C (Ta)

DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES file (IES)	LDVAL SLIMDL SQ 70 4W 865

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075326316	Folding box 1	145 mm x 45 mm x 110 mm	201.00 g	0.72 dm ³
4058075326323	Shipping box 40	475 mm x 298 mm x 230 mm	8546.00 g	32.56 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.