

PRODUCT DATASHEET

LED Performance Surface Mount Downlight 16 W 15 ° 3000 K Black

LED PERFORMANCE SURFACE MOUNT DOWNLIGHT | LED downlights for ceiling surface mounting



Areas of application

- Shops, supermarkets
- Public areas
- Corridors

Product benefits

- High power COB LED provides high lumen output in compact housing
- Low flicker light thanks to special electronic control gear
- Good color rendering for the best product presentation

Product features

- Available in two housing colors
- Available with color temperature: 3,000 K, 4,000 K
- Color rendering index R_a : > 90
- Power factor: > 0.9
- Initial color consistency: < 5 SDCM
- Lifetime (L70/B50): up to 30,000 h
- Type of protection: IP20
- CCC marked, CB test certificate



TECHNICAL DATA

Electrical data


Nominal wattage	16.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	0.90
Total harmonic distortion	< 20 %
Protection class	II
Operating mode	External LED driver

Photometrical data

Luminous flux	1200 lm
Luminous efficacy	75 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	90
Standard deviation of color matching	≤ 5 sdcn
Beam angle	15 °

Dimensions & Weight

Diameter	134.00 mm
Height	123.00 mm
Product weight	712.00 g
Cable length	110 mm



SURFACE DOWNLIGHT 16/20W

Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum

Mercury content	0.0 mg
-----------------	--------

Application & Mounting


Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+70 °C
Type of connection	Cable, 2-pole
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
LED module replaceable	Not replaceable

Lifespan

Lifespan L70/B50 at 25 °C	30000 h ¹⁾
Number of switching cycles	30000

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

DOWNLOAD DATA

Photometric and lighting design files	Document name
 IES file (IES)	LDPFM SURF DL 16W/930 15D

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075333536	Folding box 1	140 mm x 140 mm x 128 mm	794.00 g	2.51 dm ³
4058075333543	Shipping box 12	440 mm x 300 mm x 275 mm	10308.00 g	36.30 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.