

PRODUCT DATASHEET LED PFM DL 8 W 3000 K DALI

LED PERFORMANCE DOWNLIGHT G2 | LED downlight luminaires



Areas of application

- Offices
- Shopping malls
- Retail
- Hospitality

Product benefits

- Stylish design
- Die-cast aluminum housing for improved heat dissipation
- Good glare reduction (UGR < 19) and cut off angle up to 30° for comfortable indoor lighting
- External driver design allows for flexible change of control gear
- Low maintenance and operation costs due to long lifetime of LED
- Can be wireless controlled via cooperating with LEDVANCE LMS Bridge Superior
- Type of protection: IP54 (room side) provides additional protection against humidity

Product features

- $-\,$ Available with color temperature: 3,000 K, 4,000 K, 6,500 K
- Color rendering index R_a : > 80
- Initial color consistency: < 5 SDCM
- Long lifetime up to 50,000 h
- Available with diameter: 4 inch, 6 inch and 8 inch
- Available with wattage: 8 W, 11 W, 14 W, 17 W and 21 W



- Available with version: on/off switch, 1-10 V dimmable and DALI dimmable

TECHNICAL DATA

Electrical data

Nominal wattage	8.00 W
Nominal voltage	220240 V
Mains frequency	5060 Hz
Power factor λ	> 0.90
Total harmonic distortion	< 20 %
Protection class	П
Operating mode	External LED driver

Photometrical data

Luminous flux	840 lm
Luminous efficacy	105 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	80
Standard deviation of color matching	≤5 sdcm
Beam angle	65 °

Dimensions & Weight

Diameter	132.00 mm
Height	50.00 mm
Product weight	285.00 g



Materials & Colors

Product color	Gray
Housing color	Gray
Body material	Metal
Cover material	Polymethylmethacrylate (PMMA)

Marauny content	0.0 mg		
Mercury content	0.0 mg		
Application & Mounting			
Ambient temperature range	-20+70 °C		
Type of connection	Cable, 2-pole		
Type of protection	IP54/IP20		
Dimmable	Yes		
Type of dimming	DALI		
Mounting type	Recessed		
Mounting location	Ceiling		
Application environment	Indoor		
Mounting diameter	105.0115.0 mm		
Mounting depth	≥ 30 mm		
Replaceable light source	No		
Lifespan			
Lifespan L70/B50 at 25 °C	50000 h ¹⁾		
Number of switching cycles	30000		

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

	B	eplaceable light source (EPREL)	Not replaceable
--	---	---------------------------------	-----------------

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User instruction / safety instructions	LED PERFORMANCE DOWNLIGHT G2 DALI	
	Photometric and lighting design files	Document name	
	IES file (IES)	LDPFM DL 105 DALI 8W 830 G2	

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075348158	Folding box 1	174 mm x 74 mm x 177 mm	402.00 g	2.28 dm ³

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075348165	Shipping box 30	543 mm x 390 mm x 385 mm	13192.00 g	81.53 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.