

PRODUCT DATASHEET

TruSys® PFM VN 35 W/4000 K

TruSys® PERFORMANCE VERY NARROW | Luminaire inserts with very narrow light distribution



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Industry halls, high rack warehouse, garages, hardware stores

Product benefits

- Very directed light distribution for high rack warehouses
- Easy installation, no tools required for connection
- Energy saving and cost-effective
- Flexible application due to a range of different lumen packages and beam angles
- Rows of up to 57 (On-Off) / 66 (DALI) luminaires possible
- Versions with DALI ECG available

Product features

- Beam angle very narrow: 30°
- Click into place solution with smart click buttons
- Luminous efficacy: up to 160 lm/W
- Fixed luminaire taps
- Lumen package 5600 lm, 8000 lm, 11200 lm
- Steel-sheet housing
- Lens material: PMMA



- Type of protection: IP20
- Common family design with LEDVANCE
- Lifetime (L80/B10): up to 60,000 h


TECHNICAL DATA

Electrical data


| | |
|-------------------------------------------------------------|-----------------------|
| Nominal wattage | 35.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 190 mA |
| Inrush current | 25 A |
| Inrush current time T_{h50} | 220 μ s |
| Max. number of luminaires per miniature circuit breaker B16 | 13 |
| Max. number of luminaires per miniature circuit breaker C10 | 12 |
| Max. number of luminaires per miniature circuit breaker C16 | 19 |
| Power factor λ | > 0.90 |
| Total harmonic distortion | < 20 % |
| Protection class | I |
| Operating mode | Integrated LED driver |

Photometrical data


| | |
|----------------------------------------------|---------------------------|
| Luminous flux | 5600 lm |
| Luminous efficacy | 160 lm/W |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | ≥ 80 |
| Standard deviation of color matching | ≤ 3 sdc _m |
| Low flicker | Yes |
| Photobiological safety group acc. to EN62778 | RG1 |
| Beam angle | 30 ° |
| UGR | 21 |




TRUSYS PFM 35W 4000K VN 4x1
EUE LEDV



TRUSYS PFM 35W 4000K VN 4x1
EUE LEDV




TRUSYS PFM 35W 4000K VN



TRUSYS PFM 35W 4000K VN

Dimensions & Weight

| | |
|----------------|------------|
| Length | 1500.00 mm |
| Width | 66.80 mm |
| Height | 39.40 mm |
| Product weight | 1660.00 g |



Materials & Colors

| | |
|---------------|-------|
| Product color | White |
| Housing color | White |

| | |
|--------------------------------------------|-------------------------------|
| Body material | Steel |
| Cover material | Polymethylmethacrylate (PMMA) |
| Light emitting surface material | PMMA |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|----------------------------------------|--------------------|
| Ambient temperature range | -25...+40 °C |
| Type of connection | Plug-In connection |
| Type of protection | IP20 |
| Protection class IK (shock resistance) | IK04 |
| Dimmable | No |
| Mounting type | Suspended/Surface |
| Mounting location | Mounting rail |
| Application environment | Indoor |
| LED module replaceable | Not replaceable |
| With light source | Yes |

Lifespan

| | |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 65000 h ¹⁾ |
| Lifespan L80/B10 at 25 °C | 60000 h ¹⁾ |
| Lifespan L90/B10 at 25 °C | 50000 h |
| Number of switching cycles | 100000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Control gear

| | |
|-----------------------------|--------|
| Output current | 420 mA |
| ECG - Output ripple current | < 20 % |

Certificates & Standards

| | |
|----------------|----------------------|
| Standards | CE / CB / ENEC / EAC |
| Ball shot safe | No |




Additional product data









| | |
|-----------------------|---|
| Number of illuminants | - |
|-----------------------|---|


EQUIPMENT / ACCESSORIES


– Mounting rail with fixed integrated 5- and 8-pole cable

DOWNLOAD DATA

| Documents and certificates | | Document name |
|----------------------------------------------------------------------------------|----------------------------------------|---------------------------------------|
|  | User Instruction / Safety Instructions | UI_Trusys® TRUNKING SYSTEM PFM ON/OFF |
|  | Legal information | LS Insert Trusys PFM |
|  | Declarations of conformity | TRUSYS PFM |

| Photometric and lighting design files | | Document name |
|------------------------------------------------------------------------------------|----------------------|--------------------------------------|
|  | IES file (IES) | TRUSYS PFM 35W 4000K VN |
|  | LDT file (Eulumdat) | TRUSYS PFM 35W 4000K VN |
|  | ULD file (DIALux) | TRUSYS PFM 35W-4000K VN |
|  | UGR file (UGR table) | TRUSYS PFM 35W 4000K VN |
|  | LDC typ cone | TRUSYS PFM 35W 4000K VN 4x1 EUE LEDV |
|  | LDC typ cone | TRUSYS PFM 35W 4000K VN |
|  | LDC typ polar | TRUSYS PFM 35W 4000K VN |
|  | LDC typ polar | TRUSYS PFM 35W 4000K VN 4x1 EUE LEDV |

| CAD/BIM files | | Document name |
|------------------------------------------------------------------------------------|-------------|-------------------|
|  | CAD_STEP_3D | TRUSYS PFM INSERT |

| Tender texts | | Document name |
|------------------------------------------------------------------------------------|------------------|----------------------------------------------|
|  | Tender documents | TruSys PERFORMANCE VERY NARROW 35 W4000 K-EN |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|--------------|------------------------------|--------------------------------------|--------------|--------|
|--------------|------------------------------|--------------------------------------|--------------|--------|

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075398696 | Folding box 1 | 108 mm x 1,534 mm x 102 mm | 1835.00 g | 16.90 dm ³ |
| 4058075398702 | Shipping box 4 | 1,547 mm x 218 mm x 231 mm | 8133.00 g | 77.90 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.