

# PRODUCT DATASHEET

## TruSys® PFM N 50 W/4000 K

TruSys® PERFORMANCE NARROW | Luminaire inserts with narrow light distribution



---

### Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Industry halls, high rack warehouse, garages, hardware stores

---

### Product benefits

- Directed light distribution for high heights
- Easy installation, no tools required for connection
- Energy saving and cost-effective
- Flexible application due to a range of different lumen packages and beam angles
- Rows of up to 57 (On-Off) / 66 (DALI) luminaires possible
- Versions with DALI ECG available

---

### Product features

- Beam angle narrow: 60°
- Click into place solution with smart click buttons
- Luminous efficacy: up to 160 lm/W
- Fixed luminaire taps
- Lumen package 5600 lm, 8000 lm, 11200 lm
- Steel-sheet housing
- Lens material: PMMA
- Type of protection: IP20
- Common family design with LEDVANCE
- Lifetime (L80/B10): up to 60,000 h

## 403 Forbidden

---

## TECHNICAL DATA

### Electrical data

Nominal wattage	50.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	270 mA
Inrush current	30 A
Inrush current time $T_{h50}$	265 $\mu$ s
Max. number of luminaires per miniature circuit breaker B16	8
Max. number of luminaires per miniature circuit breaker C10	8
Max. number of luminaires per miniature circuit breaker C16	13
Power factor $\lambda$	> 0.90
Total harmonic distortion	< 20 %
Protection class	I
Operating mode	Integrated LED driver

### Photometrical data

Luminous flux	8000 lm
Luminous efficacy	160 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	$\geq$ 80
Standard deviation of color matching	$\leq$ 3 sdc <sub>m</sub>
Low flicker	Yes
Photobiological safety group acc. to EN62778	RG1
Beam angle	60 °
UGR	21

---

TRUSYS PFM 50W 4000K N

---

TRUSYS PFM 50W 4000K N

### Dimensions & Weight

Length	1500.00 mm
--------	------------

# 403 Forbidden

Width	66.80 mm
Height	39.40 mm
Product weight	1660.00 g

---

TRUSYS PFM

### Materials & Colors

Product color	White
Housing color	White
Body material	Steel
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	PMMA
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-25...+40 °C
Type of connection	Plug-In connection
Type of protection	IP20
Protection class IK (shock resistance)	IK04
Dimmable	No
Mounting type	Suspended/Surface
Mounting location	Mounting rail
Application environment	Indoor
With light source	No

### Lifespan

Lifespan L70/B50 at 25 °C	65000 h <sup>1)</sup>
Lifespan L80/B10 at 25 °C	60000 h <sup>1)</sup>
Lifespan L80/B50 at 25 °C	60000 h
Lifespan L90/B10 at 25 °C	50000 h
Number of switching cycles	100000

<sup>1)</sup> t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

# 403 Forbidden

## Control gear

Output current	620 mA
ECG - Output ripple current	< 20 %

## Certificates & Standards

Standards	CE / CB / ENEC 18 / EAC / RoHS
Ball shot safe	No
Replaceable light source (EPREL)	Not replaceable



## Additional product data






BEG subsidy	No
-------------	----

## EQUIPMENT / ACCESSORIES

- Mounting rail with fixed integrated 5- and 8-pole cable

## DOWNLOAD DATA

	Documents and certificates	Document name
	User instruction / safety instructions	User Instruction Trunking System
	Declarations of conformity	CE TRUSYS PFM 50W 4000K N AC17199

	Photometric and lighting design files	Document name
	IES file (IES)	TRUSYS PFM 50W 4000K N
	LDT file (Eulumdat)	TRUSYS PFM 50W 4000K N
	UGR file (UGR table)	TRUSYS PFM 50W 4000K N
	Light distribution curve type cone	TRUSYS PFM 50W 4000K N
	Light distribution curve type polar	TRUSYS PFM 50W 4000K N

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075393998	Folding box 1	108 mm x 1,534 mm x 102 mm	1835.00 g	16.90 dm <sup>3</sup>
4058075394001	Shipping box 4	1,547 mm x 218 mm x 231 mm	8133.00 g	77.90 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# 403 Forbidden

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# **403 Forbidden**