

PRODUCT DATASHEET TruSys® PFM ENERGY RAIL 8P 3000

TruSys® PERFORMANCE ENERGY RAIL 8 POLE | 8-pole mounting rail



Areas of application

- Industry halls, high rack warehouse, garages, hardware stores

Product benefits

- Simple installation
- High flexibility thanks to two available lengths (1500 mm, 3000 mm and 1500 mm end rail)

Product features

- Through wired with 8 core cable
- Different lenghts available
- Electrical connection internal at the first luminaire, no external connection unit required
- Steel-sheet housing
- End-Rail without electrical and mechanical connectors



TECHNICAL DATA

Dimensions & Weight

Length	3150 mm
Width	70.2 mm
Height	38.8 mm
Product weight	3260.00 g

Materials & Colors

Product color	White
	11.11.11

Application & Mounting

Ambient temperature range	-25+60 °C
Type of protection	IP20
Mounting type	Surface
Mounting location	Ceiling
With light source	No

Certificates & Standards

Standards CE

EQUIPMENT / ACCESSORIES

- Various accessories available

DOWNLOAD DATA

	Documents and certificates	Document name	
PDF	User Instruction / Safety Instructions	TRUNKING SYSTEM PFM EM	
	OAD/DIM Six-	Description of the second	

CAD/BIM files	Document name
CAD_STEP_3D	TRUSYS PFM ER 3000

Tender texts	Document name
Tender documents	TruSys PERFORMANCE ENERGY RAIL 8 POLE 3000-EN

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075299450	Shipping box 10	3,230 mm x 460 mm x 170 mm	35083.00 g	252.59 dm ³
4058075299450	Shipping box 10	3,230 mm x 460 mm x 170 mm	35083.00 g	252.59 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.