

PRODUCT DATASHEET

ECO CLASS RECIRCULATOR UVC 2X15W WT F K

ECO CLASS RECIRCULATOR | Closed germicidal UV-irradiator for wall mounting



Areas of application

- Reception areas
- Hotels
- Production and assembly facilities
- Offices
- Shops

Product benefits

- Constant air disinfection
- Safe and reliable
- 3 years guarantee

Product features

- Housing dedicated to T8 UVC G13
- Closed housing equipped with fans and switch
- Equipped with ozoneless UV tubes
- Available in two housing versions
- Wall mounting



TECHNICAL DATA

Electrical data


| | |
|---|-------------------------------|
| Nominal wattage | 54.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 245.000 mA |
| Max. number of luminaires per miniature circuit breaker B16 | 13 |
| Max. number of luminaires per miniature circuit breaker C10 | 14 |
| Max. number of luminaires per miniature circuit breaker C16 | 23 |
| Power factor λ | 0.95 |
| Protection class | I |
| Operating mode | Electronic control gear (ECG) |

Photometrical data

| | |
|--|-----|
| Photobiological safety group acc. to EN62778 | RG3 |
| Photobiological safety group acc. to EN62471 | RG3 |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 600.00 mm |
| Width | 247.00 mm |
| Height | 109.00 mm |
| Product weight | 4950.00 g |



ECO CLASS RECIRCULATOR UVC
2X15W WT F K

Materials & Colors

| | |
|-----------------|--------|
| Product color | White |
| Housing color | White |
| Body material | Steel |
| Mercury content | 5.0 mg |

Application & Mounting

| | |
|-------------------------|-------------------|
| Type of connection | Terminal |
| Type of protection | IP20 |
| Dimmable | No |
| Mounting type | Surface/Suspended |
| Mounting location | Wall |
| Application environment | Indoor |
| With light source | Yes |
| Holder designation | G13 |

Control gear

| | |
|----------------------|--------|
| ECG - Output voltage | 48 V |
| Output current | 313 mA |
| ECG - Length | 238 mm |
| ECG - Width | 36 mm |
| ECG - Height | 30 mm |

Additional product data

| | |
|-----------------------|---|
| Number of illuminants | 2 |
|-----------------------|---|

EQUIPMENT / ACCESSORIES

- Equipped with electronic control gear

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075533806 | Shipping box 1 | 641 mm x 256 mm x 122 mm | 5305.00 g | 20.02 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.