

PRODUCT DATASHEET

VALUE CEILING 50 W 6500 K

LED VALUE CEILING | Wall and ceiling luminaires

Areas of application

- Corridors
- Entrances / Hallways



Product benefits

- Direct connection to AC power supply thanks to integrated control gear
- Long lifetime thanks to LED technology
- Mercury-free technology
- Uniform room illumination

Product features

- Beam angle: 120°
- Color rendering index R_a : ≥ 80
- Available with color temperature: 3,000 K, 4,000 K, 6,500 K



TECHNICAL DATA

Electrical data


Nominal wattage	50.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	> 0.90
Protection class	II
Operating mode	Integrated LED driver

Photometrical data

Luminous flux	4000 lm
Luminous efficacy	80 lm/W
Color temperature	6500 K
Light color (designation)	Daylight
Color rendering index Ra	80
Beam angle	120 °

Dimensions & Weight

Diameter	500.00 mm
Height	85.00 mm
Product weight	1266.00 g



Materials & Colors

Product color	White
Housing color	White
Body material	Metal

Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

Application & Mounting

Type of connection	Terminal
Type of protection	IP20
Dimmable	No
Mounting location	Ceiling

Lifespan

Lifespan L70/B50 at 25 °C	15000 h ¹⁾
---------------------------	-----------------------

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075274440	Folding box 1	537 mm x 92 mm x 537 mm	1446.00 g	26.53 dm ³
4058075274457	Shipping box 5	558 mm x 483 mm x 566 mm	9114.00 g	152.54 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.